

The Office Coffee Experts



DIGITAL, AUTOMATIC & POUR OVER BREWERS

We are committed to offering a wide variety of brewers from manual pour overs to high volume digital brewers.

Our brewers are the latest in equipment and technology, providing greater reliability, performance and durability.

- » [Digital Brewers](#)
- » [Automatic Brewers](#)
- » [Telescoping Brewers](#)
- » [Pour Over Brewers](#)
- » [High Volume Digital Brewers](#)

DIGITAL BREWERS

Café Barista – 8-Series

"Brew 1" and "Brew 2" selectors provide a choice of two adjustable flavor profiles or portion sizes.

Water Volume may be adjusted thru the digital display: thirty ounces to one gallon.

Digital Display counts down the minutes and seconds remaining until the basket has finished draining. Visa-Brew time may be adjusted.

Water Temperature may be adjusted between 170 and 210 degrees Farenheit from the front touch pad.

Pre-infusion wets the coffee grounds to de-gas fresh roasted coffee in the basket so that the grounds may be evenly saturated during the brew cycle.

Pulse Brewing pulses your chosen water temperature onto the coffee bed for ultimate taste profile accuracy.

Water Filtering Light offers service operators an opportunity to communicate added value to customers by indicating that fresh water is being drawn into the tank through the filtration system.

Audible Signal alerts user when the filter basket has finished draining. Your fresh hot coffee is ready!

Power Conservation allows energy saving during idle time.

Service Light indicates the appropriate time for scheduled maintenance and accompanies five "Error" messages when operation is interrupted by a fault.

Cycle Counter monitors the number of brew cycles.

Filter Monitor alerts the customer when it is time to change the water filter.

Coffee Monitor Light indicates the freshness of the last beverage brewed.

Dimensions: 9 1/2"W x 18 5/16"D x 26 3/8"H

New Digital Technology!



AUTOMATIC BREWERS

FC Series FCTD Model

- 1400 watt tank heater
- Brew indicator light
- Auto Arm
- Stainless finish with black face plate
- 8 1/2"W x 17 3/8"D x 27 3/8"H

Accommodates 3.0 liter airpots & 2.5 liter thermal dispenser with sight gauge.

Dump valve brew operation for better overall brew temperatures and extremely accurate brew volumes.

Hot water faucet provides lots of piping hot water for allied products.

- * Shown here with T-Tek Thermal Dispenser (details under [accessories](#))
- * Available in FCLD (short dispenser) Model (8 1/2"W x 16 3/8"D x 21 3/16"H)



TELESCOPING BREWERS

ACE Series

One brewer for all of your server applications...from the tallest gravity server to the shortest hand held...this brewer accepts them all!!

Capable of height adjustment to suit all of your thermal servers or site dimensions. Coupled with our new "Super Board", the Telescope Brewer could support your total programme requirements from size to gourmet brewing profile!!

- "New Super Board" - activate / deactivate the following popular standard features:
 - Half brew/full brew
 - Auto Arm
 - Pulse water inlet
- Available in ACE and FC series
- Brew / Ready light
- 1400 watt tank heater
- Hot water faucet
- PDS valve (ACE model only)
- Visa-Brew
- 8 1/2"W x 16 3/8"D x 18 1/2"- 29 1/2"H



POUR OVER BREWERS

AK Series AKD Model

- 1400 watt tank heater
- Master power switch
- Ready light
- 8 1/2"W x 17 3/8"D x 26 5/8"H

Ready light incorporated for optimum brewing temperatures.

Durable stainless steel construction.

Dispenser model with brew thru lid keeps coffee hot for up to 8 hours.

85 oz. capacity dispenser allows you to dispense coffee while brewing.

- * Shown here with T-Tek Thermal Dispenser (details under [accessories](#))
- * Available in AKLD (short dispenser) Model (8 1/2"W x 16 3/8"D x 20 5/16"H)



The most popular family of pour over brewers!

HIGH VOLUME DIGITAL BREWERS

PrecisionBrew™ Digital Shuttle Brewers

Model PBIC-330

Single Vacuum Insulated Shuttle® Brewer

Model PBIC-330 is a single, digitally controlled brewer. It includes (1) VS-1.5S Shuttle® with stand (as shown).

The VS-1.5S Shuttle® is a 1.5 gallons (5.7L) vacuum insulated, stainless steel container with stand. It is portable and will maintain freshly brewed coffee hot without additional heat.

The following brew variables are programmable through the front display: Water temperature, brew volume, pulse brewing sequence, bypass percentage, low temp/no brew.

Precise brew temperature – The brewer will hold the brew temperature to +/- 1°F during the complete brew cycle.

3 Brew Volumes – From ½ gallon (1.9L) to 1 ½ gallons (5.7L). Each volume can be set by "teach" mode to eliminate trial-and-error set-up.

Dimensions: 12 1/2"W x 17 3/4"D x 36"H

* Also available in a Twin Model PBIC-430 (as shown) (22 1/2"W x 17 3/4"D x 36"H)



- info@globalcoffee.ca - (604) 618-7505 -

© globalcoffee.ca